

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 22.10.2018

Version number 4

Revision: 19.10.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: JOHA Oil varnish la, color varnish**
- **UFI-Code:** WC60-M0UE-W00T-S7HG
- **Article number:**
2221 yellow, 2222 golden yellow, 2223 red, 2224 brown, 2225 amber,
2226 golden brown, 2227 red brown, 2228 black, 2229 dark brown
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** For laquering a instrument.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Hammerl GmbH & Co. KG
Geigenlacke / Violin varnishes
Hauptstraße 18
91083 Baiersdorf
Phone +49 (0)9133 2330
Fax +49 (0)9133 5171
e-mail joha@hammerl.com
- **1.4 Emergency telephone number:**
Giftinformationszentrale Universitätsklinikum Mainz
International
24h Emergency number in German and English
Phone: +49 6131 19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

(Contd. on page 2)

GB

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 22.10.2018

Version number 4

Revision: 19.10.2018

Trade name: JOHA Oil varnish la, color varnish

(Contd. of page 1)

· Hazard statements

- H226 Flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Labelling of packages where the contents do not exceed 125 ml**· Hazard pictograms**

GHS02 GHS07

· Signal word Warning**· Hazard statements**

- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards**· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients**· 3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

EC number: 918-481-9	Kohlenwasserstoffe, C10-C13, n- Alkane, Isoalkane ringförmig <2% Aromagehalt	10-25%
	Asp. Tox. 1, H304	

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.10.2018

Version number 4

Revision: 19.10.2018

Trade name: JOHA Oil varnish la, color varnish

(Contd. of page 2)		
EC number: 919-857-5	Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cyclene, <2% Aromaten Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	≥10-<20%
CAS: 107-98-2 EINECS: 203-539-1	1-methoxy-2-propanol Flam. Liq. 3, H226	2.5-10%
EC number: 920-134-1	Kohlenwasserstoffe, C9-C11, n-Alkane, Isoalkane, Cyclene <2% Aromaten Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	2.5-10%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	≤2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Sand. Do not use water.
CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 22.10.2018

Version number 4

Revision: 19.10.2018

Trade name: JOHA Oil varnish la, color varnish

(Contd. of page 3)

- Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

107-98-2 1-methoxy-2-propanol

WEL	Short-term value: 560 mg/m ³ , 150 ppm
	Long-term value: 375 mg/m ³ , 100 ppm
Sk	

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

(Contd. on page 5)

GB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.10.2018

Version number 4

Revision: 19.10.2018

Trade name: JOHA Oil varnish Ia, color varnish

(Contd. of page 4)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Appearance:**

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value: Not determined.

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	162 °C

Flash point: 24 °C

Flammability (solid, gas): Not applicable.

Ignition temperature: 230 °C

Decomposition temperature: Not determined.

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower:	0.7 Vol %
Upper:	6.4 Vol %

Vapour pressure: Not determined.

Density: Not determined.

Relative density: Not determined.

Vapour density: Not determined.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.10.2018

Version number 4

Revision: 19.10.2018

Trade name: JOHA Oil varnish la, color varnish

(Contd. of page 5)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content: Organic solvents:	7.2 %
· Solids content:	34.9 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**107-98-2 1-methoxy-2-propanol**

Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	13,000 mg/kg (rabbit)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.

(Contd. on page 7)

GB

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 22.10.2018

Version number 4

Revision: 19.10.2018

Trade name: JOHA Oil varnish la, color varnish

(Contd. of page 6)

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.

Type of test Effective concentration Method Assessment**107-98-2 1-methoxy-2-propanol**

LC50 (48h)	23,300 mg/l (daphnia magna)
LC50 (96h)	>6,800 mg/l (gol)
EC50 (3h)	>1,000 mg/l (Pseudomonas Putita)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR** 1263 PAINT RELATED MATERIAL
- **IMDG, IATA** PAINT RELATED MATERIAL

(Contd. on page 8)

GB

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 22.10.2018

Version number 4

Revision: 19.10.2018

Trade name: JOHA Oil varnish la, color varnish

(Contd. of page 7)

· 14.3 Transport hazard class(es)**· ADR, IMDG, IATA****· Class** 3 Flammable liquids.
· Label 3**· 14.4 Packing group****· ADR, IMDG, IATA** III**· 14.5 Environmental hazards:** Product contains environmentally hazardous substances: Naphtha (petroleum), hydrodesulfurized heavy**· Marine pollutant:** No**· 14.6 Special precautions for user** Warning: Flammable liquids.**· Danger code (Kemler):** 30**· EMS Number:** F-E, S-E**· Stowage Category** A**· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.**· Transport/Additional information:****· ADR****· Limited quantities (LQ)** 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging:
30 mlMaximum net quantity per outer packaging:
1000 ml**· Transport category** 3**· Tunnel restriction code** D/E**· IMDG****· Limited quantities (LQ)** 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging:
30 mlMaximum net quantity per outer packaging:
1000 ml**· UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, 3, III**SECTION 15: Regulatory information****· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****· Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 9)

**Safety data sheet**

according to 1907/2006/EC, Article 31

Printing date 22.10.2018

Version number 4

Revision: 19.10.2018

Trade name: JOHA Oil varnish la, color varnish

(Contd. of page 8)

· Hazard pictograms

GHS02 GHS07

· Signal word Warning**· Hazard statements**

- H226 Flammable liquid and vapour.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU

- Named dangerous substances - ANNEX I** None of the ingredients is listed.
- Seveso category** P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· National regulations:**· Waterhazard class:**

Water hazard class 3 (Self-assessment): extremely hazardous for water.

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Abteilung Umweltschutz**· Contact:** Hr. Hammerl**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 10)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.10.2018

Version number 4

Revision: 19.10.2018

Trade name: JOHA Oil varnish la, color varnish

(Contd. of page 9)

IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * **Data compared to the previous version altered.**

GB